

PROSORT 421 & 431

• STANDARD SPECIFICATIONS

INTERMEDIATE & TAIL BED—21 in. deep x 1 ½ x 7/8 in flange 10 ga. formed steel channel frame, powder painted.

DRIVE/CATENARY BED—38 in. deep x 4 ga. formed steel channel frame, powder painted.

CARRYING CHAIN—Dual strands of No. 100 pre-lubricated o-ring roller chain with precision bearings and extended pins.

CHAIN LUBRICATOR—Installed at infeed end to lubricate carrying chains. Gravity feed with 24 volt DC on/off switch. Flow control valves to control the amount of oil allowed to flow to each of the brush applicators.

FLIGHTS—Anodized aluminum slat supported at each end by bushings and extended chain pins on 2 ½ in. centers.

DIVERT SHOES—Low friction molded base with high friction pusher face. Steel guide pin for switching and ball bearing cam follower for diverting. Located on 5 in. centers.

SWITCH ASSEMBLY—Pneumatic operated high speed switch assembly mounted with rubber isolators for quietness and easily removable for maintenance.

AIR REQUIREMENTS—Free air consumption at 60 psi equals .0033 cu. ft. per divert.

AIR VALVE—High speed 24 volt DC single solenoid 4-way air valve at each divert station.

AIR FILTER, REGULATOR—Supplied for main air supply line with ½ in. NPT ports. Required working pressure of 60 psi.

AIR PRESSURE SWITCH—Install in main air line near the last divert switch. Used to detect low air pressure and turn off drive.

SMART PROXIMITY SWITCHES—24 volt DC inductive proximity switch. One at each divert. Requires maintained electrical signal for duration of each divert.

SAFETY SWITCHES—Switches located at infeed and discharge ends to detect stray divert shoes or internal jams. Additional switch supplied at 30 ft. intervals. Interrupts power to drive motor when these conditions are detected.

DRIVE—Shaft mounted gearmotor. Mounted at discharge end on the opposite side from the diverts. 230/460V-3Ph. 60Hz. Horsepower based on speed and length requirements. Speeds available up to 600 FPM.

VARIABLE SPEED CONTROLLER—Provides smooth acceleration of drive motor and speed variations if necessary.

CONVEYING SPEED—Determined by application requirements.

PACKAGE SIZE—Minimum 9 in. long x 4 in. wide.

CAPACITY—Maximum load 50 lbs. per ft. Maximum unit load 100 lbs.

INDUCTION CONVEYOR—Belt conveyor slave driven from sorter at same speed as sorter.

FLOOR SUPPORTS—Not supplied as standard. See optional equipment.

• STANDARD SPECIFICATIONS - INDUCTION CONVEYOR

BELT—Black, high-grip, longitudinal groove with high speed lacing, belt width is 6 in. less than overall width.

BED—12 ga. Galvanized slider pan mounted in 6 ½ in x 12 ga. Painted formed steel channel frame.

DRIVE—Slave driven at same speed as sorter via timing belt and bolted directly to infeed of sorter. Access holes designed into side plate for ease of pulley removal.

DRIVE PULLEY—8 in. dia. with 1 1/16 in. dia. shaft at bearings-Machine-crowned.

TAKE-UP PULLEY—6 in. dia. with 1 1/16 in. dia. shaft at bearings-Machine crowned.

TAIL PULLEY—2 ¼ in dia.-Machine crowned and easily removable.

TAKE-UP—Take-ups in drive provide 16 in. of belt take-up.

BEARINGS—Sealed, pre-lubricated, self-aligning, ball bearings on drive.

FLOOR SUPPORTS—Adjustable MHS type supports. Holes in feet for lagging to floor. Vibration pads between channel and supports. Supplied to match elevation of sorter.

Sorter Conveying Surface Width	Sorter Between Rail Width "BR"	Sorter Overall Width "OAW"	Induction Bed Width "OAW"	Spur Width "OAW"	CONVEYOR SECTION									
					Drive (not including gearmotor)		Tail (not including induction belt)		Divert section with 22 degree diverter ProSort 421		Divert section with 30 degree diverter ProSort 431		Intermediate with no Diverter	
					Length	Wt. (LBS)	Length	Wt. (LBS)	Length	Wt. (LBS)	Length	Wt. (LBS)	Length	Wt. (LBS)
15"	30"	33"	18"	24"	54"	1251	36"	511	78"	704	60"	545	9" to 120" on 3" increments	104
21"	36"	39"	24"	30"		1322		551	93"	879	72"	687		110
27"	42"	45"	30"	36"		1393		591	108"	1072	84"	838		116
33"	48"	51"	36"	42"		1464		631	123"	1278	96"	1000		122
39"	54"	57"	42"	48"		1536		671	138"	1498	108"	1182		128

All weights in catalog are conveyor weights only. Accessories, crating, etc., are not included.

• OPTIONAL EQUIPMENT

FLOOR SUPPORTS—Adjustable MHS type with knee braces. Holes in feet for lagging to floor. Specify elevation. Vibration pads between channel and supports.

GUARD RAIL—6 ½ in. high solid side guards on shoe side only.

FLIGHT TUBES—1 ½ in. dia. plated tubing supported at each end by bushings and extended chain pins on 2 ½ in. centers.

PROSORT LOGIX CONTROL PACKAGE—Provides complete controls for proper sorter operation. Consult factory for details.

PROSORT 422 and 432—For sorting to both sides, speeds up to 600 FPM. Contact factory.

GEARMOTOR WEIGHT	
HP	LBS
5	181
7.5	209
10	254
15	287
20	584
25	695
30	728
40	849

